



### DESCRIPTION

Fibreglass filler. It is characterised by a special ease of modelling and high abrasive granularity. The possibility of using high abrasive granularities (coarse grinding P120 - P150) and the adaptation of the hardness of the filler to painted coatings eliminates the formation of transition between the filler and the repaired surface. In this way, the filler can be used directly underneath the filled filler. For filling unevenness on steel, aluminium and polyester (GRP) surfaces.

Designed for hand or machine dry polishing. Easy to shape even on more complex shaped surfaces, even when applying thicker coats. Abrasives do not stick during grinding. It has a very good adhesion to the substrate, it is used among other things to reinforce the weakened area of sheet metal repair, increasing the mechanical strength of the repaired element.


### TECHNICAL DATA

**VOC:** <250 g/l 2004/42/IIb (b) (250) < 250

### PREPARATION AND RECOMMENDED APPLICATION



**Surface preparation:** Clean well the surface to be treated. Make sure it is dry and free from silicone, wax and grease. On paints, primers or undercoats sand and clean before application.



**Mixing ratio:** 2-3 % paste hardener  
Pot-life 3-5' at 20°C



**Application medium:** Spatula application.

**\*Recommended spatulas for application:**

- 2004-001720 KIT 4 METALLIC SPATULAS
- 2004-001540 WHITE RUBBER SPATULA
- 2004-001620 KIT 5 PLASTIC SPATULAS



**Air drying:** 16-30' at 20° C.



**Infrared drying:** 4'-5' at 1 m.



**Recommended sanding sheets:**

P100 – P320

## CLEANING OF TOOLS

With cleaning solvent.

- 2004-001700 SPATULA CLEANER
- 2004-001701 STAR BRITE FOR SPATULA CLEANER

## SECURITY INFORMATION

See Safety Data Sheet.

## WARNING

Using too much hardener can lead to discolouration of the top coat. It is not recommended to use filler below 15°C.

**CONTINUATION OF APPLICATION**

Use:

- Easy Filler 4000 (Light Grey, Dark Grey, White and Black).
- HS Filler 540 (White, Grey and Black).

**AVAILABLE PACKAGING**

Code	Description	Packaging
5001-001030	FILL GLASS	500KG

\*For more information about our products or means of application, please visit our website [www.carrepairsystem.eu](http://www.carrepairsystem.eu) or send us an e-mail to [info@carrepairsystem.eu](mailto:info@carrepairsystem.eu)

*The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.*