



## TECHNICAL DATA SHEET



### DESCRIPTION

Low specific weight polyester putty with a very creamy texture. VOC content less than 250 g/l, limit of the European standard category and very creamy texture. Easy application with a spatula with an exceptionally smooth finish.

- Excellent adhesion on zinc-coated and aluminium sheet.
- Exceptional drying, application and sanding.
- Very fine finish.
- Supports over 100°C without distortion
- Envelope applicable with any of the Car Repair System rigs.

### SURFACES

Applicable on zinc-plated sheet, aluminium and its alloys, iron, steel, fibreglass, original paints or well consolidated old paints.


### TECHNICAL DATA

**VOC:** <250 g/l 2004/42/IIIB (b) (250) <250 g/l

### PREPARATION AND RECOMMENDED APPLICATION



**Surface preparation:** Degrease and sand with P80-P120 abrasive.



**Mixing ratio:** 1-3% (\*with benzoyl peroxide)

Mixture life 3-5'; at 20° C (\* the higher the temperature, the shorter the pot life).

Theoretical yield \*: 7.3 m<sup>2</sup>/l 100 dry microns.



**Application medium:** Spatula application.

\*Recommended spatulas for application:


- 2004-001720 KIT 4 METALLIC SPATULAS
- 2004-001540 WHITE RUBBER SPATULA
- 2004-001620 KIT 5 PLASTIC SPATULAS



**Air drying:** < 30' at 20° C



**Infrared drying:** 4'-5' at 1 m.



**Recommended sanding sheets:**

P80-P120 recess

P180-P220 finishing

## SOLID CONTENT

87-88%

## CLEANING OF TOOLS

With cleaning solvent.

- 2004-001700 SPATULA CLEANER
- 2004-001701 STAR BRITE FOR SPATULA CLEANER

## SPECIFIC WEIGHT

1,30 + - 0,05

### RAW MATERIAL

Unsaturated polyester resin, pigments, mineral fillers and solvents.

### SECURITY INFORMATION

See Safety Data Sheet.

### PRODUCT LIFE

12 months if conditions of storage are respected.

### WARNING

Do not use the product at temperatures below 5°C.

Store in a cool, dry place.

*\* The theoretical yield does not contemplate the relative loss of the application.*

### CONTINUATION OF APPLICATION

Use:

- Easy Filler 4000 (Light Grey, Dark Grey, White and Black).
- HS Filler 540 (White, Grey and Black).

### ENVASES DISPONIBLES:

Code	Description	Packaging
5001-006106	FILL MULTILIGHT PLUS WHITE	1L
5001-006107	FILL MULTILIGHT PLUS BEIGE	1L
5001-006108	FILL MULTILIGHT PLUS WHITE CART	1100ML

**COMPLEMENTARY PRODUCTS**

<b>Code</b>	<b>Description</b>
5001-006109	FILLER DISPENSER CARTRIDGE 1100ML (To dispense FILL MULTILIGHT PLUS WHITE CART (5001-006108).

\*For more information about our products or means of application, please visit our website [www.carrepairsystem.eu](http://www.carrepairsystem.eu) or send us an e-mail to [info@carrepairsystem.eu](mailto:info@carrepairsystem.eu)

*The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.*