



### DESCRIPTION

QUICK TEX is a paint formulated with thermoplastic acrylic resins with textured finish, especially for bumpers and side panels.

### CHARACTERISTICS

- Very fast drying.
- Good adhesion.
- Easy application and recoating.
- High hiding power.

PHYSICAL CHARACTERISTICS			
Binding type	Modified thermoplastic acrylic		
Colour	Black, grey		
Textured	Fine		
Dried to touch (ASTM D-1640 ISO 1517)	15'		
Dry film thickness	15 µ/coat (2 coat)		
Adhesion	100 %		
Theoretical coverage	1,8 m <sup>2</sup> for aerosol 400 ml		
Thinner	Xylene		
Product life	> 2 años		
Recoat	After 15'		
Application conditions	Ambient temp. min: 8 °C	Surface temp. min: 5-50°C	Humidity máx: 85 % R.H.P.

PACKAGING CHARACTERISTICS	
Nominal capacity	400 ml
Container heat resistance	<50 °C
Propellant	DME

## APPLICATION

Recommended for use in the automotive industry and especially for bumper painting.

- Shake the aerosol very well before use, approximately one minute after hearing the noise of the mixer.
- Apply on clean and dry surfaces. Remove corrosion with a wire brush.
- Apply in thin coats for best results, three thin coats are always better than one thick coat, recoatable after ten minutes with the same paint.
- Do not apply to connected equipment and use in well ventilated areas.

## STORAGE AND SHELF LIFE

12 months, if kept under proper storage conditions.

## AVAILABLE PACKAGING

Code	Description	Packaging
5004-001034	QUICK TEX BLACK	400ML
5004-001049	QUICK TEX GREY	400ML

\*For more information about our products or means of application, please visit our website [www.carrepairsystem.eu](http://www.carrepairsystem.eu) or send us an e-mail to [info@carrepairsystem.eu](mailto:info@carrepairsystem.eu)

*The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.*