



DESCRIPTION

Structure Coat is a textured spray that restores the structure to damaged plastics or automotive exterior parts such as dashboards, trims, center console and foot pegs.

- Reproduction of the structure in damaged plastics and plastic parts.
- Transparent color for light tones, black for dark tones.
- Simple application that saves time.
- Suitable for exterior plastic car parts, door frames, mirrors, tuning parts and bumpers, as well as interiors dashboard, center console, door panels and foot pegs.

TECHNICAL DATA

Binder base: Vinylcopolymers

Color: black

Odor: Solvent

Glossy degree: (measuring angle 60 ° acc. To DIN 67530 glossy: > 15 gloss units

Yield: Depends on the nature and color of the background: 400 ml is sufficient for 1.0 - 1.5 m²

Substrate: Damaged areas of all interior and exterior plastic parts that can be painted after applying Structure Coat textured spray.

Drying time (at 20 ° C, 50% Relative air humidity):

Dust dry: after approx. 10 minutes

Dry to the touch: after approx. 30 minutes

Drying time depends on ambient temperature, degree of humidity and number of layers applied.

Thermal resistance: Up to 80 ° C

Storage stability:

10 years in optimal conditions (= 10 ° -25 ° C, relative air humidity max. 60%)

Size: Aerosol can, nominal maximum volume 400 ml

VOC-value: 244.1g

APPLICATION

- Thoroughly clean the surface
- The damaged area must be dry and free of dust and grease
- Shake vigorously for 2 minutes
- Carry out the spray test
- Density and structural effect depend on the number of layers and the spray distance
- Apply several thin coats to obtain the desired texture
- Repaint once it has **dried for approx. 15-20 min (20 ° C)**
- **Re-paintable**


If you are using Structure Coat textured spray it will be easy to smooth out any unevenness as it can be sanded very easily after drying. Frame adjustments can also be carried out in a simple way. For example: If the surface has become too rough because the application has been too thick. Once dry you can sand and finely apply the black structure spray one more time. Our recommendation: Use a piece of cardboard to test the spraying process before the actual application by painting at different distances.




2 min




depends on
effect



20°C=15-20
min



2-3 min



STORAGE AND SHELF LIFE

12 months, if kept under proper storage conditions.

AVAILABLE PACKAGING

Code	Description	Packaging
5004-001051	STRUCTURE COAT BLACK	400ML

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.