



## TECHNICAL DATA SHEET



### DESCRIPTION

ONIX PLUS is an emulsion polish with micro abrasive particles with maximum cutting power and gloss especially suitable for paint finishing work on freshly painted and cured, deep scratch resistant surfaces.

- Smart Progressive Abrasion Technology (SPA) Plus.
- Maximum cutting power and gloss.
- No drying out of the polishing paste.
- Low temperature emission.
- The paste is free of waxes, silicones and unpleasant odours.

Its composition allows a great cutting power and speed. Easily removes sanding marks from P1000 and above.

### CHARACTERISTICS

- **Physical state** Emulsion
- **Colour** white
- **Odour** Chemical emulsion
- **Initial boiling point and boiling range** 100
- **Flash point** >61 °C
- **Ignition temperature in °C** >200
- **PH** 7,8
- **Viscosity** 25000-30000 mPa s
- **Relative density** 1.08 g/cm<sup>3</sup>

## **TECHNICAL DATA**

**Cutting power** 6 (6)

**Brightness level** 4 (6)

**Protection level** 1 (6)

**Maximum recommended sanding:** P1000

### **Varnish type**

Conventional Varnish: Yes

Scratch resistant varnish: Yes

### **Varnish condition**

Old Paint: Yes

Fresh Paint: Yes

### **Application**

By hand: Yes

By machine: Yes

### **Speed polisher**

Rotary. 700 - 1000 RPM

Rotary orbital. 700 - 1000 RPM

## **APPLICATION**

- Can be applied by hand or with a polisher.
- Start using the polisher at 700RPM and finish at 1000RPM.
- Use in combination with wool beret, or extra high cut green sponge (T120) (REF:2004-007081/2004-007084/2004-007087).
- Can be easily cleaned with a microfibre cloth.
- Use suitable protection (gloves and goggles) for application.
- Suitable for all types of paints and varnishes.

## **STORAGE**

In its original packaging, stored in a dry and well-ventilated place, at temperatures between +15°C and +25°C, it has a shelf life of 24 months from the date of manufacture.

**SAFETY INFORMATION**

See Safety Data Sheet.

**AVAILABLE PACKAGING**

Code	Description	Packaging
5010-000018	ONIX PLUS	1KG

\*For more information about our products or means of application, please visit our website [www.carrepairsystem.eu](http://www.carrepairsystem.eu) or send us an e-mail to [info@carrepairsystem.eu](mailto:info@carrepairsystem.eu)

*The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.*