

QUICK 1K EASY FILLER SPRAY

400ML

REF: 5011-001062



DESCRIPTION

1K Easy Filler is a 1K acrylic filler with the best possible filling and covering power. High film thickness in just one pass. Bonds very well to steel, aluminium, polyester filler and many plastics.

APPLICATION SURFACE

Ideal for repairs and repainting of parts.

CHARACTERISTICS

- Very high filling capacity and coverage.
- Adheres very well to steel, aluminium, polyester filler, old hardened coatings, many plastics such as PC, PVC, ABS, PA, SAN, PU, UP, EP
- Resistant to silicone remover.
- Easy wet and dry sanding
- Simple and time-saving operation.
- Quick drying.
- It can be overcoated with water and solvent based basecoats.

ENVIRONMENT AND LABELLING

Environmentally conscious: the product is committed to formulations without restricted or critical ingredients and to achieve the best possible performance. Caps and packaging are made of recyclable material.

Disposal: consider the waste inside the containers. Completely empty containers can be used for recycling. If cans are not emptied, they should be disposed of as "special waste".

Tagged

All products comply with the current status of their labelling regulations. Classification and distinction are made according to the current legal form of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) or, rather, according to CLP regulations 1272/2008 / EG. Our safety data sheets comply with the current form of REACH 1907/2006 / EG, article 31 and appendix II.

TECHNICAL DATA

Binder base	Acrylic resin
Colour	Black
Smell	Solvent
Efficiency	400ml is sufficient for approx. 1.2 m ²
Substrate	sheet steel, aluminium, polyester filler, old hardened paints and the following plastics: PC, PVC, ABS, PA, SAN, PU, UP, EP
Drying	air: 60 Min. at 20°C IR: 15 - 20 Min.
Coat thicknesses:	3 passes, approx. 70 - 80 µ
Storage stability	10 years under favourable conditions.
Size	Aerosol cans, max. nominal volume 400 ml
VOC	250,3g

MODE OF APPLICATION

Before use, read carefully and observe the warning texts on the label.

- Remove all the rust from the damaged area and sand the damaged area
- The damaged area must be dry and free of dust and grease.
- Shake the can well for 2 minutes.
- Carry out the spray test.
- Please note: at higher layer thicknesses, the drying time will be extended.
- For professional use only.
- Wear a suitable respirator (we recommend type A2 / P3).

SECURITY INFORMATION

See Safety Data Sheet.

PACKAGING AVAILABLE:

Code	Description	Packaging
5011-001060	QUICK 1K EASY FILLER SPRAY WHITE	400ML
5011-001061	QUICK 1K EASY FILLER SPRAY GREY	400ML
5011-001062	QUICK 1K EASY FILLER SPRAY BLACK	400ML

*For more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu.

Technical specifications and suggestions are based on our own experience. We guarantee the perfect quality of the product. However, considering that the conditions of each specific use are beyond our control, we cannot be held responsible for the results obtained.